

JVC®

The Perfect Experience / —

14-INCH COLOUR
VIDEO MONITOR

TM-A14E

High-Performance Preview
Monitor for Broadcast, Production,
Education, and CCTV Applications



- PAL/NTSC Compatibility
- CPU Picture Control
- 7U Rack Mountable

- Built-in Speaker
- Lightweight Moulded Cabinet
- Detachable AC power cable

High-Quality, Multi-Function Preview Monitor

The TM-A14E provides the powerful features, the simplicity, and the versatility needed for a wide range of applications in fields which include broadcasting, education, and closed circuit TV monitoring.

■ Multi-Standard Compatibility

The TM-A14E accepts both PAL and NTSC signals. Its automatic detection function identifies the input signal and selects the corresponding mode.

■ CPU Picture Control

A built-in central processing unit (CPU) is programmed with default parameters including contrast, brightness, chroma, and phase. Users can simply change settings through the controls located on the front panel.

■ Rack Mount Adapter

Using the optional rack mount adapter (RK-A14E), you can install the compactly designed TM-A14E in a standard EIA 19-inch rack.

■ Built-in Speaker

The compact, high-quality speaker built into the front panel of the TM-A14E delivers an output of 1 W.

■ Lightweight Moulded Cabinet

The CRT is housed in a lightweight, black moulded cabinet.

■ Detachable AC power cable

The TM-A14E comes with a detachable AC power cable for enhanced operating flexibility.

Specifications


Type	Colour video monitor
Colour system	PAL/NTSC, Auto select
CRT	14" (diagonally measured), in-line guns, stripe pitch of 0.65 mm
Scanning frequency	H: 15.625 kHz (PAL)/15.75 kHz (NTSC) V: 50/60 Hz
Horizontal resolution	320 TV lines
Power requirement	230 V AC, 50/60 Hz under CE
Power consumption	0.5 A
Colour temperature	6,500°K
Input terminals	
1. Input A: Composite video	1.0 V (p-p), 75 ohms, negative sync., auto-termination, BNC x 2, bridged-out possible
2. Input B: Composite video	1.0 V (p-p), 75 ohms, negative sync., auto-termination, BNC x 2, bridged-out possible
Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync. C: 0.3 V (p-p), 75 ohms (PAL) 0.286 V (p-p), 75 ohms (NTSC)
Audio terminals	RCA pin x 4 for input A and input B channels, bridged-out possible
Audio speaker	8 cm round, 1 W output
Power cord	Continental type UK Mains Lead type
Weight	9.5 kg
Option	7U rack mountable

Rear Panel




Dimensions

Unit: mm



Front Panel



RK-A14E
Optional Rack Mount Adapter

JVC®

DISTRIBUTED BY

Design and specifications subject to change without notice.